

Quick Hinge Breach Door Systems



Quick Hinge Breach Door System
with Fixed Steel Frame

Recognizing that many of our customers have access to salvage or surplus doors, we also offer the **Adjustable Frame Quick Hinge Door System** that accommodates the three most common door widths – 30, 32, and 36 inch with varying thicknesses from 1-3/8" to 1-3/4". The Quick Hinge mechanism and the adjustable frame are simple, fast and easy to use – maximizing valuable training time and providing a robust, flexible and cost effective breaching training aid.

Adaptable to your training needs, the **Quick Hinge Breach Door System** is provided with pre-drilled mounting tabs for permanent installation in existing training facilities, shoot houses, or breach bays. An optional base allows it to be a mobile, free-standing training system that can be transported to alternate sites.

Range Systems **Quick Hinge Breach Door Systems** allows training to be conducted using commercial off-the-shelf doors to provide realistic breaching using real doors with real door properties. There are no ballistic pins to insert or replace, no special panels to install, and no tools required to employ the **Quick Hinge Breach Door System**. Minimal set-up requirements and quick reset intervals ensures maximum training time and low-cost consumables makes the Quick Hinge Breach Door System economical.

Quick Hinge Breach Door Systems are available in two models; **Fixed Frame** and **Adjustable Frame**. Both breach door systems support all mechanical, shotgun, and explosive breaching techniques and allow you to choose the door type so you have flexibility for mission specific training. The heavy gauge steel **Fixed Frame** accepts standard 36" width wood and steel doors (hollow and solid core) which insert easily into the frame and are quickly secured by tightening hand-knob clamp screws. The frame accepts door thicknesses from 1-3/8" to 1-3/4".



Quick Hinge Breach Door System
with Adjustable Steel Frame