

Product Overview

The Pro-Touch Series Master Controller is available with either a fixed-position 15-inch touchscreen or an 11-inch mobile tablet, providing range personnel with flexible, centralized control of the entire range. Ranges can be equipped with up to two Master Controllers, allowing any combination of fixed and mobile units to best suit operational requirements.

Operators can assign shooters to individual lanes, set lane times, monitor target carrier strike detection, and manage lanes independently or as grouped configurations.

The intuitive, high-resolution interface provides complete lane control, including target lighting, lane status, remaining session time, assistance requests, and real-time strike detection alerts. Range Masters can group multiple lanes for coordinated operation or lock out selected lanes or the entire range during cold range events, enhancing both safety and operational efficiency.



Key Features & Benefits

- **User-Friendly Touchscreen:** Intuitive touchscreen operation with a clear color display showing lane status and real-time conditions.
- **Efficient Lane Management:** Eliminates the need for a separate range timer. For commercial ranges, the Master Control allows easy monitoring and management of lane rental time, streamlining check-ins and lane transitions.
- **Strike Monitoring:** Alerts the range officer to errant rounds striking the carrier, enhancing safety and ensuring proper shooting discipline.
- **Cease Fire Button:** Instantly returns all lanes to the home position and shuts down the range, providing a quick and effective safety measure when needed.
- **Lane Assignment & Personalization:** Allows for lane assignment options to personalize the shooter's experience, ensuring a customized and efficient training session.

PRO-TOUCH SERIES MASTER CONTROL SPECIFICATIONS

Dimensions	
Master Control	15.34" x 9.83" x 0.88"
Portable Master Control	10.12" x 6.64" x 0.27"
Enviromental	
Master Control	0°C to 40°C / 32°F to 104°F
Portable Master Control	0°C to 40°C / 32°F to 104°F
Power	
Master Control	120VAC/1.5A-240VAC/0.75A
Portable Master Control	7,040 mAh lithium-ion battery 15W wired charging
Screen Size	
Master Control	15.6" diagonal, Active matrix TFT LCD (LED)
Portable Master Control	11" diagonal, Active matrix TFT LCD (LED)